



Manufacturer of Inflatable Packers, Flow Control Valves, Pitless Units and other products for investigating, controlling and producing the EARTH'S FLUIDS.™

Email: info@baski.com
 Website: www.baski.com

Phone: 1-303-789-1200 • 1-800-55-BASKI
 FAX: 1-303-789-0900

SPECIFICATION SHEET:

Packer Model MD-2.4

Medium Duty, Sliding-Head Type (USA Pat. No. 4,455,027)

Dimensions and Confined/Unconfined Test Pressures:

Uninflated O.D., max.	2.4"	61 mm
Largest recommended hole size	4.5"	114 mm
Mandrel pipe size, nominal	3/4"	19 mm
Approximate mandrel pipe I.D.	0.74"	19 mm
Uninflated element length, min.	40"	1,016 mm
Tested unconfined to	500 psi	35 bar
Tested confined in a 3-1/2" (89 mm) chamber to	1,000 psi	70 bar

Differential Pressure Rating (DPR): in single packer applications, for specific hole sizes

Cased or Competent Hole Size		Maximum Differential Pressure Rating	
inches	mm	psi	bar
3.0	76	900	60
3.5	89	900	60
4.0	102	500	35
4.5	114	250	15

Please call factory for DPR in straddle packer applications.

Construction and Materials:

Element	Construction	Fully-reinforced (reinforcing the entire length of element)
	Materials	Reinforced natural rubber, with outer covering of natural rubber
	Connection to ends	7" (178 mm) high strength steel Continuous Crimp Collar
Heads	Connection	1/8" NPT inflation ports, top and bottom
Mandrel	Pipe	3/4" Schedule 80 pipe
	Material	Type 304 stainless steel
	Connection	3/4" NPT, top and bottom
Other	Metal Parts	Aluminum

Accessories:

In-Line Adapter	Model ILA0.75	3/4" nominal pipe size, Aluminum, 8 top ports Includes an assortment of brass fittings for sealing electrical leads in varying diam., 3/16", 1/4", 3/8"
-----------------	---------------	--

Shipping Data:

Approx. net weight	30 lbs.	14 kg
Approx. net length	67"	1,700 mm

Pricing and Terms:

Please call for pricing, FOB Denver factory and valid for 60 days.
 Our terms are prepay (wire transfer, Visa, MasterCard, or certified check).
 Company checks require approximately two (2) weeks to clear.