

Email: <u>info@baski.com</u>
Website: www.baski.com

Manufacturer of Inflatable Packers, Flow Control Valves, Pitless Units and other products for investigating, controlling and producing the EARTH'S FLUIDS.TM

Phone: 1-303-789-1200 • 1-800-55-BASKI

FAX: 1-303-789-0900

SPECIFICATION SHEET:

Packer Model MD-5.5

Medium Duty, Sliding-Head Type (USA Pat. No. 4,455,027)

Dimensions and Confined/Unconfined Test Pressures:

Uninflated O.D., max.	5.5"	140 mm
Largest recommended hole size	10.5"	267 mm
Mandrel pipe size, nominal	2-1/2"	64 mm
Approximate mandrel pipe I.D.	2.32"	59 mm
Uninflated element length, min.	50"	1,270 mm
Tested unconfined to	500 psi	35 bar
Tested confined in a 8" (203 mm) chamber to	900 psi	60 bar

Differential Pressure Rating (DPR): in single packer applications, for specific hole sizes

Cased or Ma		num	
Competent		Differential	
Hole Size		Pressure Rating	
mm	psi	bar	
152	1,300	90	
178	1,200	85	
203	900	60	
229	600	40	
241	400	30	
267	300	20	
	etent Size mm 152 178 203 229 241	etent Difference Size Pressure mm psi 152 1,300 178 1,200 203 900 229 600 241 400	

Please call factory for DPR in straddle packer applications.

Construction and Materials:

Element	Construction Materials	Fully-reinforced (reinforcing the entire length of element) Reinforced natural rubber, with
		outer covering of natural rubber
	Connection to ends	14" (356 mm) high strength steel Continuous Crimp Collar
Heads	Connection	1/4" NPT inflation ports, top and bottom
Mandrel	Pipe	2-1/2" nominal
	Material	high strength stainless steel, chrome plated
	Connection	2-1/2" NPT, top and bottom
Other	Metal Parts	Aluminum and stainless steel

Accessories:

In-Line Adapter	Model ILA2.5	2-1/2" nominal pipe size, Aluminum, 8 top ports
		Includes an assortment of brass fittings for sealing
		electrical leads in varying diam., 3/16", 1/4", 3/8"

Shipping Data:	Approx. net weight	175 lbs.	79 kg
	Approx. net length	96"	2,438 mm

Pricing and Terms: Please call for pricing, FOB Denver factory and valid for 60 days.

Our terms are prepay (wire transfer, Visa, MasterCard, or certified check).

Company checks require approximately two (2) weeks to clear.

updated May 20, 2004 specifications subject to change without notice MD55_specs_rev6b